

Super 10

Spreader til frostvanning 12x12m



Super10 Performance Table

Precipitation rates (mm/hr) and uniformity (CU) at various spacing

Nozzle Color	P (bar)	Q (l/h)	D (m)	Precipitation rates (mm/hr) Spacing (m)					
				9x9	9x10	10x10	9x12	10x12	12x12
Blue	2.5	360	18	4.5	4.0	3.6			
	3.0	395	17.5	4.9	4.4	3.9			
	3.5	425	17	5.3	4.8	4.3			
	4.0	455	17	5.6	5.1	4.6			
F.R.	3.0-5.0	360	18	4.5	4.1	3.7			
Yellow	2.5	450	20	5.7	5.1	4.6	4.3	3.8	3.2
	3.0	495	20	6.1	5.5	4.9	4.6	4.1	3.4
	3.5	530	20	6.6	5.9	5.3	4.9	4.4	3.7
	4.0	570	20	7.1	6.4	5.7	5.3	4.8	4.0
F.R.	3.0-5.0	450	20	5.5	5.0	4.5	4.2	3.7	3.1
Green	2.5	550	20	6.7	6.0	5.4	5.0	4.5	3.8
	3.0	600	20	7.4	6.7	6.0	5.5	5.0	4.2
	3.5	650	20	8.0	7.2	6.5	6.0	5.4	4.5
	4.0	695	20	8.6	7.8	7.0	6.5	5.8	4.8
F.R.	3.0-5.0	550	20	6.9	6.2	5.6	5.2	4.3	3.9
Red	2.5	670	21	8.3	7.4	6.7	6.2	5.6	4.6
	3.0	735	21	9.0	8.1	7.3	6.8	6.1	5.1
	3.5	790	21	9.6	8.7	7.8	7.2	6.5	5.4
	4.0	850	21	10.5	9.4	8.5	7.9	7.1	5.9
F.R.	3.0-5.0	670	21	8.3	7.5	6.7	6.2	5.6	4.7

Color code - Distribution uniformity | CU < 85% | CU 85-88% | CU 88-92% | CU > 92%

F.R. = Flow Regulator

**f BRØDR.
FREBERG AS**

Tønsberg

Tlf. 33 30 86 60 post@freberg.no Fax: 33 30 86 61